



Copper Gasket Cement

Product Description

VHT® Copper Gasket Cement has been formulated with the same ingredients as our world-renowned high temperature coatings. It maintains excellent adhesion under severe pressure and heat fluctuations. This high metallic formula assures tight seals on cork, paper, and metal gaskets. This product has been exclusively tested on racing engines in the field and on dynamometers. It has met and exceeded the high compression and high temperature requirements of these mega horsepower engines.

Product Characteristics

Color: Copper Gasket

Properties

Product Weight: 6.15 lb/gal
Flash Point: Propellant < 0° F

Coating System

VHT provides a multi-high performance coating for the ultimate in protection and quality.

Coat SP21A Copper Gasket

Application

Prepare gasket contact surface by removing the old gasket materials with the proper tools. Wipe surface down with the grease and wax remover.

Shake can vigorously for one full minute after mixing ball moves freely. Shake it for 10 seconds after each minute of use. Lay the gasket down on a piece of cardboard. Spray on a thin coat, just enough to evenly cover the surface on both sides of the gasket. Use at temperatures between 60° F (16° C) and 95° F (35° C).

Wait 5 minutes or until film becomes tacky. Apply gasket to surface and tighten as soon as possible (within 2 hours).

Packaging

Fill Weight: 12.11 oz
Per Case: 6 cans
Case Weight: 6.08 lbs
Cases/Pallet: 156
Units/Pallet: 936 cans

Uses

Head Gaskets, Rubber Hoses, Cork Gaskets, Water Pump Gaskets, Threaded Fittings, AN Fittings, Paper Gaskets, Oil Pan Gaskets, and Metal Gaskets.

Surfaces:

- Metal, Rubber, Cork, and Paper